

Resinate UltraCast Resin

SECTION 1. IDENTIFICATION

Product name : Resinate UltraCast Resin

Manufacturer or supplier's details

Company name of supplier : Polymer Science Corp
Address : 6027 79 Ave SE, Calgary,
AB T2C 5P1 Canada

Telephone : 403-287-2751

Emergency telephone number : Canutec (613) 996 – 6666 (24 hours)

Recommended use of the chemical and restrictions on use

Recommended use : Component of a Epoxy Coating or Casting System.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Acute toxicity (Oral) : Category 4

Acute toxicity (Dermal) : Category 4

Serious eye damage : Category 1

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 + H312 Harmful if swallowed or in contact with skin.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Resinate UltraCast Resin

P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

P302 + P352 + P312 IF ON SKIN: Wash with plenty of water. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

Storage:

Not available

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Propylidynetrimehanol, propoxylated, reaction products with ammonia	39423-51-3	80 - 100

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.

Resinate UltraCast Resin

- In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : No data is available on the product itself.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
-

Resinate UltraCast Resin

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Neutralise with acid.
 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 To avoid spills during handling keep bottle on a metal tray.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Keep in properly labelled containers.

Materials to avoid : For incompatible materials please refer to Section 10 of this SDS.

Further information on storage stability : Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
 Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing

Resinate UltraCast Resin

problems.

- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : light yellow
- Odour : ammoniacal
- Odour Threshold : No data is available on the product itself.
- pH : 11.6
- Melting point/range : Not applicable
- Freezing point : < -20 °C
- Initial boiling point and boiling range : No information available.
- Flash point : 218.5 °C
Method: closed cup
- Evaporation rate : No data is available on the product itself.
- Flammability (solid, gas) : No data is available on the product itself.
- Flammability (liquids) : No data is available on the product itself.
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : 6.82 hPa (20 °C)
- Relative vapour density : 1
- Relative density : No data is available on the product itself.
- Density : 0.9658 g/cm³ (20 °C)
Method: Relative Density
- Solubility(ies)
Water solubility : 562 g/l (20 °C)

Resinate UltraCast Resin

Solubility in other solvents	:	No data is available on the product itself.
Partition coefficient: n-octanol/water	:	log Pow: -1.13 (20 - 25 °C) pH: 12.7 Method: Partition coefficient
Auto-ignition temperature	:	320 °C
Decomposition temperature	:	236 °C
Self-Accelerating decomposition temperature (SADT)	:	No data is available on the product itself.
Viscosity		
Viscosity, kinematic	:	110 mm ² /s
Explosive properties	:	No data is available on the product itself.
Oxidizing properties	:	None. Method: Directive 67/548/EEC, Annex V, A.21
Molecular weight	:	No data available
Metal corrosion rate	:	Not corrosive to metals
Particle size	:	No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No hazards to be specially mentioned.
Conditions to avoid	:	None known.
Incompatible materials	:	None known.
Hazardous decomposition products	:	carbon dioxide carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxic

Resinate UltraCast Resin

Acute oral toxicity - Product : LD50 (Rat, male and female): 550 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : No data available

Acute dermal toxicity - Product : LD50 (Rat, male and female): > 1,000 mg/kg
Method: OECD Test Guideline 402

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Components:**

Propylidynetrimethanol, propoxylated, reaction products with ammonia:
Species: Rabbit
Method: OECD Test Guideline 404
Result: Mild skin irritation

Serious eye damage/eye irritation**Components:**

Propylidynetrimethanol, propoxylated, reaction products with ammonia:
Result: Irreversible effects on the eye
Method: OECD Test Guideline 405

Respiratory or skin sensitisation**Components:**

Propylidynetrimethanol, propoxylated, reaction products with ammonia:
Exposure routes: Skin
Species: Guinea pig
Result: Does not cause skin sensitisation.

Assessment: No data available

Germ cell mutagenicity**Product:**

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Metabolic activation: Metabolic activation
Method: OECD Test Guideline 482
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Product:

Resinate UltraCast Resin

Genotoxicity in vivo : Cell type: Somatic
Application Route: Intraperitoneal injection
Dose: 2.5 mg/kg
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

No data available

Carcinogenicity - Assessment : No data available

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Reproductive toxicity**Product:**

Effects on fertility : Species: Rat, male and female
Application Route: Dermal
Method: OECD Test Guideline 421

Components:

Propylidynetrimehanol, propoxylated, reaction products with ammonia:

Effects on foetal development : Species: Rat
Application Route: Oral
Dose: 0, 10, 100, 125, 200 mg/kg
General Toxicity Maternal: No-observed-effect level: > 100 mg/kg body weight
Embryo-foetal toxicity: No-observed-effect level: > 100 mg/kg body weight
Method: OECD Test Guideline 414

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity**Components:**

Propylidynetrimehanol, propoxylated, reaction products with ammonia:

Species: Rat, male and female
NOAEL: \geq 100 mg/kg
Application Route: Oral
Exposure time: 90 d
Dose: 0, 10, 75, 100, 150, 200 mg/kg

Resinate UltraCast Resin

Method: OECD Test Guideline 408

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

Other health hazards

No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:**

Propylidynetrimethanol, propoxylated, reaction products with ammonia:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Resinate UltraCast Resin**Components:**

Propylidynetrimethanol, propoxylated, reaction products with ammonia:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 13 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Components:

Propylidynetrimethanol, propoxylated, reaction products with ammonia:

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 4.4 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 1 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : No data available

Toxicity to fish (Chronic toxicity) : No data available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : No data available

M-Factor (Chronic aquatic toxicity) : No data available

Components:

Propylidynetrimethanol, propoxylated, reaction products with ammonia:

Toxicity to microorganisms : EC50 (activated sludge): ca. 1,000 mg/l
Exposure time: 0.5 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209

Toxicity to soil dwelling organisms : No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment

Resinate UltraCast Resin

Acute aquatic toxicity	: No data available
Chronic aquatic toxicity	: No data available
Toxicity Data on Soil	: No data available
Other organisms relevant to the environment	: No data available

Persistence and degradability**Components:**

Propylidynetrimethanol, propoxylated, reaction products with ammonia:

Biodegradability	: Concentration: 100 mg/l Result: Not readily biodegradable. Biodegradation: < 5 % Exposure time: 28 d Method: OECD Test Guideline 301F
------------------	---

Biochemical Oxygen Demand (BOD)	: No data available
---------------------------------	---------------------

Chemical Oxygen Demand (COD)	: No data available
------------------------------	---------------------

BOD/COD	: No data available
---------	---------------------

ThOD	: No data available
------	---------------------

BOD/ThOD	: No data available
----------	---------------------

Dissolved organic carbon (DOC)	: No data available
--------------------------------	---------------------

Physico-chemical removability	: No data available
-------------------------------	---------------------

Components:

Propylidynetrimethanol, propoxylated, reaction products with ammonia:

Stability in water	: Degradation half life(DT50): > 1 yr (25 °C) pH: 7.5 Method: OECD Test Guideline 111 Remarks: Fresh water
--------------------	--

Photodegradation	: No data available
------------------	---------------------

Impact on Sewage Treatment	: No data available
----------------------------	---------------------

Bioaccumulative potential

Bioaccumulation	: No data available
-----------------	---------------------

Partition coefficient: n-octanol/water - Product	: log Pow: -1.13 (20 - 25 °C) pH: 12.7
--	---

Resinate UltraCast Resin

Method: Partition coefficient

Mobility in soil

Mobility : No data available

Distribution among environmental compartments : No data available

Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential Not applicable

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Dispose of as hazardous waste in compliance with local and national regulations. Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

Resinate UltraCast Resin**SECTION 14. TRANSPORT INFORMATION****International Regulations****TDG**

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(TRIMETHYLOLPROPANE POLYOXYPROPYLENE
TRIAMINE)
Class : 9
Packing group : III
Labels : 9

IATA

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(TRIMETHYLOLPROPANE POLYOXYPROPYLENE
TRIAMINE)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo
aircraft) : 964
Packing instruction
(passenger aircraft) : 964

IMDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(TRIMETHYLOLPROPANE POLYOXYPROPYLENE
TRIAMINE)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**TDG**

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(TRIMETHYLOLPROPANE POLYOXYPROPYLENE
TRIAMINE)
Class : 9

Resinate UltraCast Resin

Packing group : III
Labels : 9
ERG Code : 171
Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**The components of this product are reported in the following inventories:**

CH INV : On the inventory, or in compliance with the inventory
DSL : All components of this product are on the Canadian DSL
AICS : On the inventory, or in compliance with the inventory
NZIoC : On the inventory, or in compliance with the inventory
ENCS : On the inventory, or in compliance with the inventory
KECI : On the inventory, or in compliance with the inventory
PICCS : On the inventory, or in compliance with the inventory
IECSC : On the inventory, or in compliance with the inventory
TCSI : On the inventory, or in compliance with the inventory
TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

Canada. CEPA 1999 Significant New Activity (SNAc) List


No substances are subject to a Significant New Activity Notification.

Resinate UltraCast Resin

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Revision Date : 03/06/2020

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.